



Treppendetails Maßstab 1:20  
Staircase details scale 1:20

Alle Stahlteile gestrichen

- 1 Eichenholz-Leiste 12/35 mm
- 2 Stahlprofil 20/35 mm
- 3 Flachstahl 6/35 mm
- 4 Stahlwinkel aus verschweißten Profilen 2x 20/25 mm, auf Bodenplatte geschraubt
- 5 Bodenaufbau: Eichenparkett 15 mm, versiegelt  
Heizestrich 85 mm  
Trittschalldämmung 5 mm  
Hartschaumdämmung 20 mm  
Stahlbetondecke 250 mm
- 6 Gasbetonmauerwerk 365 mm mit Kalkputz 20 mm
- 7 Vollholz Eiche 35 mm, mit Blinddübeln befestigt
- 8 Filzunterlage 3 mm
- 9 Ortbetonlauf

All steel members painted

- 1 12/35 mm oak strip
- 2 20/35 mm steel section
- 3 6/35 mm steel flat
- 4 steel angle, consisting of 2x 20/25 mm flats welded together, bolted to floor slab
- 5 floor construction: 15 mm oak parquet, sealed; 85 mm screed around underfloor heating 5 mm impact-sound insulation 20 mm rigid foamed plastic insulation 250 mm reinforced concrete floor
- 6 365 mm expanded concrete blockwork with 20 mm lime plaster
- 7 35 mm oak boarding fixed with concealed dowels
- 8 3 mm felt underlay
- 9 insitu concrete stair flight

